



## PERFORMANCE SPECIFICATION

### FAMOGREEN CU P4

Revised 01/01/03

Famogreen CU P4 is a high-grade polymeric bitumen sheet with plasto-elastic properties. It is modified with age stabilizing amorphous polyalphaolefin (APAO). The unique thermally bonded copper/polyester inlay provides both strength and rust resistance making this superior quality membrane a first choice in vegetated roofing applications. The low temperature flexibility along with its heat stability qualities allow this membrane to be used in both intensive and extensive Green Roof Systems. This heat welded membrane can be used in the field of the roof and/or as a flashing membrane.

#### Composition:

Inlay:	Special root protector, non-woven polyester with copper film
Bottom Side:	Meltable polyethylene film
Top:	Silica sand
Roll Length:	7.5 m (24 ft 6 in)
Roll Width:	1.0 m (3 ft 3 in)
Roll Weight:	39 kg (86 lb)
Normal Thickness:	4.0 mm (160 mil)
Quantity/pallet	25 rolls/pallet
	187.5 m <sup>2</sup> (2,018 ft <sup>2</sup> )

#### Technical Data:

<b>Thickness:</b>	4.0 mm (160 mil)
<b>Inlay:</b>	Special root resistant polyester with copper film, having a unit weight of 350 g/m <sup>2</sup> (10.3 oz/yd <sup>2</sup> ).
<b>Tensile Strength:</b>	MD: >800 N/5cm (90 lbf/in) XMD: >600 N/5cm (67 lbf/in)
<b>Elongation:</b>	MD: >35% XMD: >35%

1033 Downshire Chase, Virginia Beach, VA 23452  
Telephone: (757) 340-4201 Fax: (757) 431-3172  
E-Mail: perrymd@att.net

**Low Temperature Flex:** <-20°C (-4°F)  
**Heat Stability:** >150°C (302°F)  
**Asbestos Content, %:** Zero